

## SELBSTSICHERNDE STECKVERBINDER - CONEX

90°-Winkelstück mit zylindrischem  
Außengewinde - RPC MG



Pression min. d'utilisation - EU

0 / 10 bar

Min/Max Temperatur

0 / 60 °C

| Art. Nr    | AG   | Abm. A (mm) | Abm. B (mm) | Abm. C (mm) | Abm. D (mm) | Abm. E (mm) |
|------------|------|-------------|-------------|-------------|-------------|-------------|
| RPC MG04M5 | M5   | 25          | 17.5        | 10          | 21          | 10          |
| RPC MG0400 | G1/8 | 24.1        | 17.5        | 12          | 18.6        | 10          |
| RPC MG0401 | G1/4 | 24.7        | 17.5        | 14          | 18.7        | 10          |
| RPC MG05M5 | M5   | 27.5        | 20.5        | 12          | 23.5        | 12.8        |
| RPC MG0500 | G1/8 | 27          | 20.5        | 12          | 21.5        | 12.8        |
| RPC MG0501 | G1/4 | 27.5        | 20.5        | 14          | 21.5        | 12.8        |
| RPC MG0502 | G3/8 | 29          | 20.5        | 17          | 22.5        | 12.8        |
| RPC MG0503 | G1/2 | 30          | 20.5        | 21          | 22          | 12.8        |
| RPC MG06M5 | M5   | 27.5        | 20.5        | 12          | 23.5        | 12.8        |
| RPC MG0600 | G1/8 | 27          | 20.5        | 12          | 21.5        | 12.8        |
| RPC MG0601 | G1/4 | 27.5        | 20.5        | 14          | 21.5        | 12.8        |
| RPC MG0602 | G3/8 | 29          | 20.5        | 17          | 22.5        | 12.8        |
| RPC MG0603 | G1/2 | 30          | 20.5        | 21          | 22          | 12.8        |
| RPC MG0800 | G1/8 | 29.2        | 22.5        | 14          | 23.7        | 13.8        |
| RPC MG0801 | G1/4 | 29.2        | 22.5        | 14          | 23.2        | 13.8        |
| RPC MG0802 | G3/8 | 30.7        | 22.5        | 17          | 24.2        | 13.8        |
| RPC MG0803 | G1/2 | 31.7        | 22.5        | 21          | 23.7        | 13.8        |
| RPC MG1000 | G1/8 | 33.7        | 26.3        | 17          | 28.2        | 16.8        |
| RPC MG1001 | G1/4 | 34.2        | 26.3        | 17          | 28.2        | 16.8        |
| RPC MG1002 | G3/8 | 34.2        | 26.3        | 17          | 27.7        | 16.8        |
| RPC MG1003 | G1/2 | 35.2        | 26.3        | 21          | 27.2        | 16.8        |
| RPC MG1201 | G1/4 | 35          | 27.8        | 19          | 29          | 19.8        |
| RPC MG1202 | G3/8 | 34.5        | 27.8        | 19          | 28          | 19.8        |
| RPC MG1203 | G1/2 | 36          | 27.8        | 21          | 28          | 19.8        |
| RPC MG1402 | G3/8 | 38.2        | 29.8        | 22          | 31.7        | 22.7        |
| RPC MG1403 | G1/2 | 37.2        | 29.8        | 24          | 29.2        | 22.7        |
| RPC MG1602 | G3/8 | 41.5        | 30.8        | 24          | 34.9        | 23.8        |
| RPC MG1603 | G1/2 | 39          | 30.8        | 24          | 31          | 23.8        |