

SELBSTSICHERNDE STECKVERBINDER - CONEX

90°-Winkelstück mit konischem
Außengewinde - RPC MR



Pression min. d'utilisation - EU

0 / 10 bar

Min/Max Temperatur

0 / 60 °C

Art. Nr	AG	Abm. A (mm)	Abm. B (mm)	Abm. C (mm)	Abm. D (mm)	Abm. E (mm)
RPC MR0400	R1/8	25	17.5	10	17.5	10
RPC MR0401	R1/4	26.5	17.5	14	17.5	10
RPC MR0500	R1/8	27.5	20.5	12	20	12.8
RPC MR0501	R1/4	29	20.5	14	20	12.8
RPC MR0502	R3/8	31.5	20.5	17	20.5	12.8
RPC MR0503	R1/2	34	20.5	21	21	12.8
RPC MR0600	R1/8	27.5	20.5	12	20	12.8
RPC MR0601	R1/4	29	20.5	14	20	12.8
RPC MR0602	R3/8	31.5	20.5	17	20.5	12.8
RPC MR0603	R1/2	34	20.5	21	21	12.8
RPC MR0800	R1/8	29.5	22.5	14	22	13.8
RPC MR0801	R1/4	31	22.5	14	22	13.8
RPC MR0802	R3/8	33.5	22.5	17	22.5	13.8
RPC MR0803	R1/2	36	22.5	21	23	13.8
RPC MR1000	R1/8	33.2	26.3	17	25.7	16.8
RPC MR1001	R1/4	34.7	26.3	17	25.7	16.8
RPC MR1002	R3/8	36.7	26.3	17	25.7	16.8
RPC MR1003	R1/2	39.2	26.3	21	26.2	16.8
RPC MR1201	R1/4	35.5	27.8	19	26.5	19.8
RPC MR1202	R3/8	38	27.8	19	27	19.8
RPC MR1203	R1/2	40	27.8	21	27	19.8
RPC MR1402	R3/8	40	29.8	22	29	22.7
RPC MR1403	R1/2	42	29.8	22	29	22.7
RPC MR1602	R3/8	41.5	30.8	24	30.5	23.8
RPC MR1603	R1/2	43.5	30.8	24	30.5	23.8

Gewinde Teflon vorbeschichtet