

PPS SYSTEM VOLLALUMINIUM - DRUCKLUFTLEITUNGEN

PPS BT- Anbohrschelle mit
zylindrischem Innengewinde



Max. Betriebsdruck (bar)

16

Min/Max Temperatur (°C)

-20 / 80

Material

Aluminium

Art. Nr	IG		Für Rohr mit Außen-Ø	Nettogewicht (Kg)	Abm. A (mm)	Abm. B (mm)	Abm. C (mm)
PPS1 BT2512	G1/2	G1/2	25	0.19	32	82	70
PPS1 BT2517	G3/8	G3/8	25	0.195	32	82	70
PPS1 BT3212	G1/2	G1/2	32	0.176	32	82	70
PPS1 BT3227	G3/4	G3/4	32	0.176	32	84	70
PPS1 BT4012	G1/2	G1/2	40	0.58	44	110	102
PPS1 BT4027	G3/4	G3/4	40	0.565	44	110	102
PPS1 BT4034	G1	G1	40	0.55	44	110	102
PPS1 BT5012	G1/2	G1/2	50	0.513	44	110	102
PPS1 BT5027	G3/4	G3/4	50	0.5	44	110	102
PPS1 BT5034	G1	G1	50	0.49	44	110	102
PPS1 BT6312	G1/2	G1/2	63	1,2	57	161	147
PPS1 BT6327	G3/4	G3/4	63	1.17	57	161	147
PPS1 BT6334	G1	G1	63	1.12	57	162	147
PPS1 BT8012	G1/2	G1/2	80	1.09	57	161	147
PPS1 BT8027	G3/4	G3/4	80	1,06	57	161	147
PPS1 BT8034	G1	G1	80	1,02	57	162	147