

PPS SYSTEM VOLLALUMINIUM - DRUCKLUFTLEITUNGEN

PPS1 MF - Aluminiumrohr-
Übergangsstück mit zylindrischem
IG



Max. Betriebsdruck (bar)

16

Min/Max Temperatur (°C)

-20 / 80

Material

Aluminium

Art. Nr	IG		Für Rohr mit Außen-Ø	Nettogewicht (Kg)	Abm. A (mm)	Abm. B (mm)	Abm. C (mm)
1. PPS1 MF1617	G3/8	G3/8	16	0.047	32	53	26
1. PPS1 MF1612	G1/2	G1/2	16	0,046	32	53	26
1. PPS1 MF2012	G1/2	G1/2	20	0.069	38	63	32
1. PPS1 MF2027	G3/4	G3/4	20	0.066	38	63	32
1. PPS1 MF2512	G1/2	G1/2	25	0.128	46	72	38
1. PPS1 MF2527	G3/4	G3/4	25	0.124	46	72	38
1. PPS1 MF2534	G1	G1	25	0.117	46	72	38
1. PPS1 MF3234	G1	G1	32	0,211	57	83	46
1. PPS1 MF3242	G1 1/4	G1 1/4	32	0,184	57	83	46
1. PPS1 MF4042	G1 1/4	G1 1/4	40	0.32	68	98	57
1. PPS1 MF4049	G1 1/2	G1 1/2	40	0.34	68	103	57
1. PPS1 MF5049	G1 1/2	G1 1/2	50	0.563	84	110	72
1. PPS1 MF5060	G2	G2	50	0.531	84	115	72
1. PPS1 MF6360	G2	G2	63	0.965	100	137	90
1. PPS1 MF6376	G2 1/2	G2 1/2	63	0.942	100	142	90
1. PPS1 MF8076	G2 1/2	G2 1/2	80	1.53	121	164	110
1. PPS1 MF8090	G3	G3	80	1.45	121	164	110
2. PPS1 MF10090	G3	G3	100	4.22	211	186.5	