


## PPS SYSTEM VOLLALUMINIUM - DRUCKLUFTLEITUNGEN

PPS1 RSIF - Kugelhahn mit  
einseitigem zylindrischem IG



Max. Betriebsdruck (bar)

16

Min/Max Temperatur (°C)

-20 / 80

Material

Aluminium

| Art. Nr                 | IG     |        | Für Rohr mit<br>Außen-Ø | Nettogewicht<br>(Kg) | Abm. A (mm) | Abm. B (mm) | Abm. C (mm) | Abm. D (mm) |
|-------------------------|--------|--------|-------------------------|----------------------|-------------|-------------|-------------|-------------|
| 1. PPS1<br>RSIF1612     | G1/2   | G1/2   | 16                      | 0.257                | 32          | 121         | 64          | 25          |
| 1. PPS1<br>RSIF2012     | G1/2   | G1/2   | 20                      | 0.284                | 38          | 121         | 66          | 25          |
| 1. PPS1<br>RSIF2527     | G3/4   | G3/4   | 25                      | 0.474                | 46          | 125         | 75          | 31          |
| 1. PPS1<br>RSIF3234     | G1     | G1     | 32                      | 0,768                | 57          | 151         | 85          | 40          |
| 1. PPS1<br>RSIF4042     | G1 1/4 | G1 1/4 | 40                      | 1.2                  | 68          | 157         | 99.09       | 49          |
| 2. PPS1 RSI-<br>FAL5049 | G1 1/2 | G1 1/2 | 50                      | 1.55                 |             |             |             |             |
| 2. PPS1 RSI-<br>FAL6360 | G2     | G2     | 63                      | 0,00264              |             |             |             |             |
| 2. PPS1 RSI-<br>FAL8076 | G2 1/2 | G2 1/2 | 80                      | 4.68                 |             |             |             |             |