


## PPS SYSTEM VOLLALUMINIUM - DRUCKLUFTLEITUNGEN

PPS1 TR - Aluminiumrohr-T-Stück  
mit Reduzierung



Max. Betriebsdruck (bar)

16

Min/Max Temperatur (°C)

-20 / 80

Material

Aluminium

| Art. Nr         | Für Rohr mit Außen-Ø | Nettogewicht (Kg) | Abm. A (mm) | Abm. B (mm) | Abm. C (mm) | Abm. D (mm) |
|-----------------|----------------------|-------------------|-------------|-------------|-------------|-------------|
| 1. PPS1 TR2016  | 20;16                | 0.144             | 66          | 108         | 38          | 32          |
| 1. PPS1 TR2516  | 25;16                | 0.265             | 78          | 131         | 46          | 32          |
| 1. PPS1 TR2520  | 25;20                | 0.271             | 83          | 131         | 46          | 38          |
| 1. PPS1 TR3216  | 32;16                | 0.429             | 91          | 155         | 57          | 32          |
| 1. PPS1 TR3220  | 32;20                | 0.435             | 96          | 155         | 57          | 38          |
| 1. PPS1 TR3225  | 32;25                | 0.46              | 102         | 155         | 57          | 46          |
| 2. PPS1 TR6350  | 63;50                | 3.4               | 100         | 264         | 248         | 84          |
| 2. PPS1 TR8063  | 80;63                | 5                 | 120         | 310         | 300         | 100         |
| 2. PPS1 TR10080 | 100;80               | 7.45              | 168         | 308         | 352         | 120         |