


PPS SYSTEM VOLLALUMINIUM - DRUCKLUFTLEITUNGEN

PPS1 TT - Aluminiumrohr-T-Stück mit
zylindrischem IG



Max. Betriebsdruck (bar)	Min/Max Temperatur (°C)	Material
16	-20 / 80	Aluminium

Art. Nr	IG		Für Rohr mit Außen-Ø	Nettogewicht (Kg)	Abm. A (mm)	Abm. B (mm)	Abm. C (mm)	Abm. D (mm)
1. PPS1 TT1617	G3/8	G3/8	16	0,089	32	90	40	26
1. PPS1 TT2012	G1/2	G1/2	20	0.126	38	108	47	32
1. PPS1 TT2512	G1/2	G1/2	25	0.246	46	131	56	38
1. PPS1 TT2527	G3/4	G3/4	25	0.235	46	131	56	38
1. PPS1 TT3227	G3/4	G3/4	32	0.401	57	155	68	46
1. PPS1 TT3234	G1	G1	32	0.38	57	155	68	46
1. PPS1 TT4027	G3/4	G3/4	40	0.69	68	183	85	57
1. PPS1 TT4034	G1	G1	40	0.67	68	183	85	57
1. PPS1 TT4042	G1 1/4	G1 1/4	40	0.615	68	183	85	57
1. PPS1 TT5034	G1	G1	50	1,2	84	219	101	72
1. PPS1 TT5042	G1 1/4	G1 1/4	50	1.13	84	219	101	72
2. PPS1 TT5049	G1 1/2	G1 1/2	50	1.85	84	219	101	72
1. PPS1 TT6334	G1	G1	63	2.17	100	261	129	90
1. PPS1 TT6342	G1 1/4	G1 1/4	63	2.12	100	261	129	90
2. PPS1 TT6349	G1 1/2	G1 1/2	63	2.07	100	261	129	90
2. PPS1 TT6360	G2	G2	63	2.9	100	261	129	90
1. PPS1 TT8034	G1	G1	80	3.45	121	315	155	110
1. PPS1 TT8049	G1 1/2	G1 1/2	80	3.35	121	315	155	110
2. PPS1 TT8060	G2	G2	80	4	121	315	155	110
2. PPS1 TT8076	G2 1/2	G2 1/2	80	2.98	121	315	155	110
3. PPS1 TT10060	G2	G2	100	5.03				
3. PPS1 TT10090	G3	G3	100	5.03	153.3	308.5	175	125