

ALARGADORES DE MANGUERA RESISTENTES A LOS ACEITES

Manguera AIRCA provistas de enchufes rápidos prevoS1



Presión max. de utilización (bar)

12

Temperatura mín/máx

-15 / 70 °C

-15.00 / 70.00 °C

-15 / 70 °C

Referencia	Longitud (m)	Ø int/ext (mm)	Perfil	Para tubo Ø int.	Ø de pasaje (mm)
RAL AISB810	10	8 / 15	ISO 6150B	8	6 mm
RAL AISB105	5	10 / 18	ISO 6150B	10	6 mm
RAL AISB1010	10	10 / 18	ISO 6150B	10	6 mm
RAL AISB1310	10	13 / 22	ISO 6150B	13	8 mm
RAL AISB1320	20	13 / 22	ISO 6150B	13	8 mm
RAL AISEB1310	10	13 / 22	ISO 6150B	13	11 mm
RAL AISEB1320	20	13 / 22	ISO 6150B	13	11 mm
RAL AISEB1610	10	16 / 25	ISO 6150B	16	11 mm
RAL AISEB1620	20	16 / 25	ISO 6150B	16	11 mm
RAL AISE1910	10	19 / 28	ISO 6150B	19	11 mm
RAL AISE1920	20	19 / 28	ISO 6150B	19	11 mm
RAL AESB810	10	8 / 15	EUROPEAN	8	7.4 mm
RAL AESB105	5	10 / 18	EUROPEAN	10	7.4 mm
RAL AESB1010	10	10 / 18	EUROPEAN	10	7.4 mm
RAL AESB1310	10	13 / 22	EUROPEAN	13	7.4 mm
RAL AESB1320	20	13 / 22	EUROPEAN	13	7.4 mm
RAL AESEB1310	10	13 / 22	EUROPEAN	13	11 mm
RAL AESEB1320	20	13 / 22	EUROPEAN	13	11 mm
RAL AESEB1610	10	16 / 25	EUROPEAN	16	11 mm
RAL AESEB1620	20	16 / 25	EUROPEAN	16	11 mm
RAL AESE1910	10	19 / 28	EUROPEAN	19	11 mm
RAL AESE1920	20	19 / 28	EUROPEAN	19	11 mm
RAL ACSB810	10	8 / 15	ISO 6150C	8	6 mm
RAL ACSB105	5	10 / 18	ISO 6150C	10	6 mm
RAL ACSB1010	10	10 / 18	ISO 6150C	10	6 mm
RAL AASB810	10	10 / 18	ARO 210	10	6 mm
RAL AASB105	5	10 / 18	ARO 210	10	6 mm
RAL AASB1010	10	10 / 18	ARO 210	10	6 mm

Prevost SAS - 15, rue du Pré Faucon - CS 90208 - Annecy-le-vieux - 74940 Annecy - France

Tél. +33 (0)4 50 64 04 45 - sales@prevost.eu - www.prevost.eu