

CONEX PUSH FITTINGS

Parallel male 90° elbow - RPC MG



Min / Max operating pressure

0 / 10 bar

Min. / Max temperature

0 / 60 °C

Part number	Male thread	Dim. A (mm)	Dim. B (mm)	Dim. C (mm)	Dim. D (mm)	Dim. E (mm)
RPC MG04M5	M5	25	17.5	10	21	10
RPC MG0400	G1/8	24.1	17.5	12	18.6	10
RPC MG0401	G1/4	24.7	17.5	14	18.7	10
RPC MG05M5	M5	27.5	20.5	12	23.5	12.8
RPC MG0500	G1/8	27	20.5	12	21.5	12.8
RPC MG0501	G1/4	27.5	20.5	14	21.5	12.8
RPC MG0502	G3/8	29	20.5	17	22.5	12.8
RPC MG0503	G1/2	30	20.5	21	22	12.8
RPC MG06M5	M5	27.5	20.5	12	23.5	12.8
RPC MG0600	G1/8	27	20.5	12	21.5	12.8
RPC MG0601	G1/4	27.5	20.5	14	21.5	12.8
RPC MG0602	G3/8	29	20.5	17	22.5	12.8
RPC MG0603	G1/2	30	20.5	21	22	12.8
RPC MG0800	G1/8	29.2	22.5	14	23.7	13.8
RPC MG0801	G1/4	29.2	22.5	14	23.2	13.8
RPC MG0802	G3/8	30.7	22.5	17	24.2	13.8
RPC MG0803	G1/2	31.7	22.5	21	23.7	13.8
RPC MG1000	G1/8	33.7	26.3	17	28.2	16.8
RPC MG1001	G1/4	34.2	26.3	17	28.2	16.8
RPC MG1002	G3/8	34.2	26.3	17	27.7	16.8
RPC MG1003	G1/2	35.2	26.3	21	27.2	16.8
RPC MG1201	G1/4	35	27.8	19	29	19.8
RPC MG1202	G3/8	34.5	27.8	19	28	19.8
RPC MG1203	G1/2	36	27.8	21	28	19.8
RPC MG1402	G3/8	38.2	29.8	22	31.7	22.7
RPC MG1403	G1/2	37.2	29.8	24	29.2	22.7
RPC MG1602	G3/8	41.5	30.8	24	34.9	23.8
RPC MG1603	G1/2	39	30.8	24	31	23.8