

RUBBER HOSE EXTENSION SET OIL RESISTANT

AIRCA hose extension with metal
safety quick couplers



Max. operating pressure (bar)

12

Min. / Max temperature

-15 / 70 °C

Part number	Length (m)	Ø int/ext (mm)	Profile	For pipe ID	ID passage (mm)
RAL AIS1610	10	16 / 25	ISO 6150B	16	11 mm
RAL AIS1620	20	16 / 25	ISO 6150B	16	11 mm
RAL AISB1610	10	16 / 25	ISO 6150B	16	11 mm
RAL AISB1620	20	16 / 25	ISO 6150B	16	11 mm
RAL AIS1910	10	19 / 28	ISO 6150B	19	11 mm
RAL AIS1920	20	19 / 28	ISO 6150B	19	11 mm
RAL AES1610	10	16 / 25	EUROPEAN	16	11 mm
RAL AES1620	20	16 / 25	EUROPEAN	16	11 mm
RAL AES1910	10	19 / 28	EUROPEAN	19	11 mm
RAL AES1920	20	19 / 28	EUROPEAN	19	11 mm
RAL AESB1610	10	16 / 25	EUROPEAN	16	11 mm
RAL AESB1620	20	16 / 25	EUROPEAN	16	11 mm
RAL ACM1310	10	13 / 22	ISO 6150C	13	8 mm
RAL ACM1320	20	13 / 22	ISO 6150C	13	8 mm
RAL ACM1610	10	16 / 25	ISO 6150C	16	11 mm
RAL ACM1620	20	16 / 25	ISO 6150C	16	11 mm
RAL ACM1910	10	19 / 28	ISO 6150C	19	11 mm
RAL ACM1920	20	19 / 28	ISO 6150C	19	11 mm
RAL ACMB810	10	8 / 15	ISO 6150C	8	6 mm
RAL ACMB1010	10	10 / 18	ISO 6150C	10	6 mm