

POLYURETHANE SPIRAL HOSES WITH QUICK COUPLING AND PLUG

Polyurethane recoils with PREVOS1
safety release quick couplers



Color	Max. operating pressure (bar)	Min. / Max temperature (°C)
Blue	8	-15 / 70

Part number	ID passage (mm)	Ø int/ext (mm)	Coil Ø	Length (m)	Net weight (Kg)
PUS 64IS	6 mm	6.5 / 10	52	4	0.545
PUS 66IS	6 mm	6.5 / 10	52	6	0.676
PUS 68IS	6 mm	6.5 / 10	52	8	0,83
PUS 86IS	6 mm	8 / 12	65	6	0,899
PUS 52ES	7.4 mm	5 / 8	42	2	0,33
PUS 54ES	7.4 mm	5 / 8	42	4	0,369
PUS 64ES	7.4 mm	6.5 / 10	52	4	0,56
PUS 66ES	7.4 mm	6.5 / 10	52	6	0.724
PUS 68ES	7.4 mm	6.5 / 10	52	8	0,854
PUS 84ES	7.4 mm	8 / 12	65	4	0,707
PUS 86ES	7.4 mm	8 / 12	65	6	0,9
PUS 88ES	7.4 mm	8 / 12	65	8	1,101