

POLYAMIDE SPIRAL HOSES

Polyamide recoils with swiveling male fittings



Color	Max. operating pressure (bar)	Min. / Max temperature (°C)
Blue	10	-20 / 90

Part number	Male thread	Ø int/ext (mm)	Coil Ø	Length (m)	Min. length (M)	Net weight (Kg)
SPIC 62	G1/4	6 / 8	96	2.5	0.12	0,178
SPIC 65	G1/4	6 / 8	96	5	0.24	0.29
SPIC 610	G1/4	6 / 8	96	10	0.48	0.45
SPIC 620	G1/4	6 / 8	96	20	0.96	0,882
SPIC 82	G1/4	8 / 10	110	2.5	0.14	0,23
SPIC 85	G1/4	8 / 10	110	5	0.28	0,35
SPIC 810	G1/4	8 / 10	110	10	0.55	0,6
SPIC 820	G1/4	8 / 10	110	20	1.1	1,026
SPIC 102	G3/8	9.5 / 12	144	2.5	0.12	0,36
SPIC 104	G3/8	9.5 / 12	144	4	0.24	0,6
SPIC 108	G3/8	9.5 / 12	144	8.5	0.49	1.11
SPIC 1016	G3/8	9.5 / 12	144	17	0.97	1,473